

SPECIFICATION

BS 2869:2010 - Class C2 - Maximum 10ppm

This product is only for use in off-road applications - not for road (taxed vehicle) purposes.

PROPERTY	UNIT	LIMITS	TEST METHODS
APPEARANCE – COLOUR @ 15 °C ¹		CLEAR & BRIGHT	VISUAL
SPECIFIC ENERGY CV	MJ/KG	42.80 MIN	
KINEMATIC VISCOSITY @ 40 DEG C	cSt MIN - MAX	1.00 – 2.00	BS EN ISO 3104
DENSITY @ 15 DEG C	KG/m ³	750 MIN	BS EN ISO 3675 / IP 365
RECOVERY RATE @ 240 DEG C	% v/v	50 MIN	BS EN ISO 3405 / 3924
RECOVERY RATE @ 200 DEG C	% v/v	15 MIN	BS EN ISO 3405 / 3924
FLASH POINT	Deg C	38 MIN	BS EN ISO 2719 / 13736
SULPHUR CONTENT	MG/KG	10	BS EN ISO 20846 / 8754
SMOKE POINT	Mm	19 MIN	BS 2000-57
CHAR VALUE	MG/KG	20 MAX	BS 2000-10
COPPER CORROSION (2hr @100°C)	Class	1 MAX	BS EN ISO 2160
ODOUR		MARKETABLE	

¹The product will be marked with HM Revenue & Customs statutory markers

* The information herein is correct to the best of our knowledge at the time of publication. Whilst Innovo Energy guarantee that our fuels meet the stated specification below, the additional or supplementary data provided is for information only and should not be construed as a specification or warrant.